Model

Vertical turret type automatic bobbin exchanger Wind-up machine with automatic handling device



Description

This Vertical turret type automatic bobbin exchanger Wind-up machine with automatic handling device is suitable wind-up machine for Re-winding and Excluder machine.

Bobbins are automatically set-up, taken-off and exchanged.

When a trouble occurres during the automatic handle, safety system operates prevent a serous accident.

Specification

Wire size range	φ0.2 ~ 0.55mm
Wire speed range	(MAX) 350m/min
Number of line	(MAX) 1-line
Wind-up machine	TASV25H (1head)
	Bobbin automatic switching over type with auto-counter. Wire break down detector with direct current control.
Wind-up bobbin	(MAX) 25kg
	PT-10, 15, 25
Traverse stroke	(MAX) 250mm
Traverse speed	(MAX) 44.5mm/sec
Handling device	3-shafts control method
Takt time	about 150 second
Power source	AC200-220V, 50/60Hz, 3-PHASE
Electric capacity	About 3kW
Machine layout	2700mm(W) x 1650mm(D) x 2500mm(H)

Address : 4-11-3, Kajihara, Takatsuki, Osaka, Japan Phone# : ++81-72-669-2181 E-mail : info@kuhara-net.co.jp

Zip-code: 569-0091 Fax#: ++81-72-669-3028 Web-site: http://www.kuhara-net.co.jp